AlVital



AT101

Fingertip Oximeter

Oksimeter OLED ringan,
cukup menggunakan satu baterai AAA.

- Tombol 5 Arah
- *Ingress Protection*
- Laya OLED
- *Micro-USB Port*
- Rotasi Layar (90° 180° 270° 360°)
- Fitur Alarm
- Otomatis Aktif/Non-aktif
- Cukup dengan Satu Baterai

Seluruh Kebutuhan Terintegrasi Dalam "Ukuran Ujung Jari".

AT101 dirancang untuk menyesuaikan berbagai pengguna dan memenuhi semua kebutuhan dalam satu perangkat yang ringkas.

Dari segi performa, AT101 memberikan hasil pengukuran yang akurat dalam hitungan detik. Desain *housing*-nya yang serbaguna dapat menyesuaikan berbagai ukuran jari

Dengan kombinasi teknologi elektronik terbaru, AT101 hadir dengan produk paling ramah pengguna dan lingkungan.

Fitur Produk

Penggunaan Mudah
- Menyala secara otomatis untuk pemeriksaan cepat.
- Layar OLED berwarna dan layar grafis untuk tampilan yang nyaman.
- Lima tombol arah untuk pengaturan yang mudah.

Alarm
- Terdapat alarm audio dan visual untuk pembacaan oksimetri/denyut nadi yang abnormal.

Konsumsi Daya Efisien
- Produk hemat energi dan ramah lingkungan.
  (satu baterai Alkaline AAA untuk penggunaan terus menerus selama 18 jam)


Pengaturan Waktu
- Fungsi *stopwatch* beserta pengukuran SpO2 untuk penghitungan napas atau penggunaan olahraga.

Distributor :

Customer Care : (021) 26075090, 26080867, 26080866
www.innovationindo.com

Specifications

Models	AT101 I (Bluetooth)	AT101 B	AT101 C
Pulse Oximetry			
Range	0% to 100%		
Resolution	1%		
Accuracy	70% to 100% range: ±2%;		
Method	less than 70%: unspecified Dual wavelength LED		
Heart (Pulse) Rate			
Range	30 to 250bpm		
Resolution	1bpm		
Accuracy	±1bpm or ±1%, whichever is greater		
Input/Output			
Auto on/off	Whenever user inserts a finger, the device will turn on automatically. Vise versa, the device will turn off automatically, when the finger is removed from it.		
LCD display	Full Color OLED		
Input Key	A push-down key for interface operation	A 5-directional key for interface operation	A push-down key for interface operation
Alarm option	Yes	Yes	No
Alarm setting	Low SpO2 alarm: setting range: 50%~ 95%; High SpO2 alarm: setting range: 80%~ 100%; Low heart rate alarm: setting range: 30BPM ~ 110BPM; High heart rate alarm: setting range: 75BPM ~ 250BPM		
Mechanical			
Weight	Without battery: < 26g (0,92 ounces)		
Size	L67.5mm(2.63") x W38mm(1.48") x H25mm(0.98")		
Battery			
Type	1 AAA Alkaline battery		
Usage life	Auto on/off features , >18-hour typical operation		
Environmental			
Operating Temperature	5° to 40° C;41°F to 104° F		
Storage Temperature	-30° to 70° C; -22° to 158° F		
Humidity	10% to 90%, non-condensing for both operating & storage		
Atmospheric Pressure	700 hPa ~ 1013 hPa for both operating and storage		
Classification			
Degree of Protection	Type BF Applied part		
Ingress Protection	IP22		
Mode of operation	Continuous use	Continuous use	Spot Check
Safety	IEC60601-1		
EMC	IEC60601-1-2		
Performance standar	ISO80601-2-61		
Standard Package			
Package Dimension	L75mm(2.95") x W60mm(2.36") x H35mm(1.38")		
Accessories	User manual X 1, AAA battery X 1		
Optional Accessories	Neck Strap (Black); Belt pouch (Black)		
Wireless connection	Bluetooth 4.0 BLE	N/A	N/A







Didistribusikan Oleh :
PT Innovation Healthcare Indonesia
Komplek Ruko Permata Kota Blok Q No. 11, Jl. Pangeran Tubagus Angke No. 170
Kel. Pejagalan, Kec. Penjaringan, Jakarta
Telp. +62-21-22663999
www.innovationindo.com